

Engine Additives & Fluids

Premium Gold Super Concentrated Oil Treatment

Added protection with high-tech CX3™ anti-wear additive
Special detergent formula with sludge-fighting additives



- Fights oil breakdown
- Cleans & quiets noisy lifters & valves

Stock# C-90, Qty.-12, 14 fl. oz. / 414 ml

Motor Flush

Cleans Engines in 3 Minutes



- Easy to use! Add to oil before changing
- Removes power-robbing deposits
- Dissolves gum, sludge & varnish
- Helps free sticking valve lifters & rings

Stock# C-19, Qty.-24, 15 fl. oz. / 443 ml

Stock# C-20, Qty.-12, 30 fl. oz. / 887 ml

Premium Concentrated Oil Treatment



- Fights oil breakdown
- Cleans & quiets noisy lifters & valves

Stock# C-91, Qty.-12, 14 fl. oz. / 414 ml
Stock# C-92, Qty.-12, 14 fl. oz. / 414 ml

Engine Stop Leak Stops Oil Leaks



- Formulated to help reduce or stop oil leaks, revitalize & condition "dried out" seals & gaskets
- Contains the same additive used and approved by car manufacturers
- Recommended for gasoline and diesel engines
- Easy to use, just add to oil

Stock# C-89, Qty.-12, 15 fl. oz. / 443 ml

UltraCoat™ Engine Treatment with CX4™ Friction Barrier Anti-wear Protection plus PTFE



- Extra protection at start-up
- Helps prolong engine life
- Reduces friction & engine wear with extreme pressure barrier protection
- Reduces fuel consumption
- Replaces 1 quart of oil

Stock# C-2000, Qty.-12, 16 fl. oz. / 473 ml

Smoke Treatment



- Formulated to thicken the protective oil barrier to help reduce exhaust smoke & oil consumption
- Reduce metal-to-metal contact
- Quiet noisy lifters, valves & pistons

Stock# C-2100, Qty.-12, 14.5 fl. oz. / 428 ml

Power Steering Fluid



- Meets service requirements of GM, Ford, Chrysler, and most imports
- Helps stop leaks & squeals
- Smooth year around performance
- Protects against wear

Stock# C-27, Qty.-12, 12 fl. oz. / 350 ml
Stock# C-28, Qty.-12, 32 fl. oz. net wt. / 946 g
Stock# C-29, Qty.-4, 1 gal. / 3.78 liter

Super Heavy Duty Brake Fluid

450°F Dot 3



- High-temp formula 450° F min. dry boiling point
- Mixes with ALL DOT 3 brake fluids
- Formulated for disc & drum brakes

Stock# C-55, Qty.-12, 12 fl. oz. / 350 ml
Stock# C-56, Qty.-12, 32 fl. oz. net wt. / 946 g
Stock# C-57, Qty.-4, 1 gal. / 3.78 liter
Stock# C-58, Qty.-1, 5 gal. / 18.9 liter