

Models & Specifications:



A. HH3901



B. HH2501



C. HH2502



D. HH3930



E. HH3970



F. HH3971



G. FM3666



H. FM3669C



I. DRL366-1

A. HH3901

Halogen Conversion Head
Converts headlight housings or other clear-lensed lights to Halogen color filtered warning lights.
Lens color: Amber, Blue, Clear, Red

B. HH2501

Mini-Rectangular Halogen Head
Grill mount Halogen warning light for emergency vehicles.
Lens color: Amber, Blue, Clear, Red

C. HH2502

Rectangular Halogen Head
Grill mount Halogen warning light for emergency vehicles.
Lens color: Amber, Blue, Clear, Red

D. HH3930

Par-36 round sealed beam head
Grill or rear mount halogen warning light with shock-resistant black rubber housing.
Lens color: Amber, Blue, Clear, Red

E. HH3970

7" diameter sealed beam head
For ambulances, fire trucks, rescue vehicles, school buses.
Lens color: Amber, Blue, Clear, Red

F. HH3971

7" Rectangular sealed beam head
For ambulances, fire trucks, rescue vehicles
Lens color: Amber, Blue, Clear, Red
Color: Clear only
Order ST413 for Amber, Blue, or Red

G. FM3666:

Flash Rate: 12V DC Mechanical Flasher.
1.2 flashes per second per lamp.

FM3661:

Flash Rate: 12V DC Solid state flasher for up to 100 Watts per side.
1.9 flashes per second per lamp.

FM3662:

Flash Rate: 12V DC Solid state flasher for up to 100 Watts per side.
2.9 flashes per second per lamp.

FM3662-24:

Flash Rate: 24V DC Solid state flasher for up to 100 Watts per side.
2.9 flashes per second per lamp.

FM3667:

Flash Rate: 12V DC Solid state flasher for back-up/brake light.
2.4 flashes per second per lamp.

FM3669:

12V DC Solid state flasher for up to 165 Watts per side.
Customer selectable flash patterns. DRL control.

H. FM3669C:

12V DC Solid state flasher for up to 165 Watts per side.
Customer selectable flash patterns.
Compatible with factory installed DRL control.

FM6901:

12V DC Solid state flasher. Alternately flashes headlights.
Has high beam override and night time cut off.
Handles up to 165 watts per output.
Flash Rate: 1.9 flashes per second per lamp.

FM6902:

12V DC Solid state flasher. Alternately flashes headlights.
Has high beam override and night time cut off.
Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.

FM6903:

12V DC Solid state flasher. Simultaneously flashes headlights. Has high beam override and night time cut off. Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.

FM6904:

Flashes left headlight three times, flashes right headlight three times, then flashes both headlights together three times. Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.

DRL366:

Daytime running light module.

I. DRL366-1:

Heavy-duty daytime running light module with taillight output, park brake override.

