

**Temperature Switches • For use with two (cold and hot) indicator lights • Self grounding.**

Heavy duty, corrosion resistant construction.

 Green light - Cold - OFF at 105°F to 117°F  
 Red light - Hot - ON at 242°F to 254°F

**⊖ No. 84224**
**Mounting stem:** 3/8"-18 dryseal thread  
 (P.T.F.) 1/2" long.

 Replaces: **Delco** F1852 **Ford** C5AZ-10884B,  
 D6LY, D6LZ-10884A **Motorcraft** SW-626,  
 SW-1345.

 Green light - Cold - OFF at 102°F to 122°F  
 Red light - Hot - ON at 233°F to 253°F

**⊖ No. 84211**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F.-S.A.E. short) 5/8" long.

 Replaces: **Delco** 198683 684,740, 741, D862

 Green light - Cold - OFF at 102°F to 122°F  
 Red light - Hot - ON at 243°F to 263°F

**⊖ No. 84213**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F. - S.A.E. short) 5/16" long.

 Replaces: **Chrysler** 2497651, 2580242, 2857562,  
 CH-2515, CH-2516, CH-2520 **Delco** 1993181,  
 303, 350, 521, 561, 580, 581, 1998189, 140, 181, 746,  
 6400211, 6402372, D-1851, D-1857, D-1860  
**G.M.** 6402778

 Green light - Cold - OFF at 87°F to 119°F  
 Red light - Hot - ON at 259°F to 291°F

**⊖ No. 84230**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F.-S.A.E. short) 5/8" long.

 Replaces: **Delco** G1861 **G.M.** 6489600, 6489903,  
 6490094, 6490452, 8992238.

**Switches for operation of one (hot) indicator light • Self grounding**

Red Light - Hot - ON at 246° F to 266° F

**No. 84229**
**Mounting stem:** 3/8"-18 dryseal thread  
 (P.T.F.) 1/2" long.

 Replaces: **Delco** F1853 **Ford** C8GY, D1FZ, D6AZ,  
 E43Z-10884A **Motorcraft** SW-663, SW-983,  
 SW-1344, SW-1344A


Red Light - Hot - ON at 232° F to 264° F

**No. 84227**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F.-S.A.E. short) 5/8" long.

 Replaces: **Delco** 1993444, 445, 508, 513,  
 582, 588, 1994061, D1858, 59, 68  
**G.M.** 6490152, 25036507 **Motorcraft** SWG-485


Red Light - Hot - ON at 239° F to 271° F

**No. 84210**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F.-S.A.E. short) 5/16" long.

 Replaces: **Delco** 1993426, 427, D-1879  
**G.M.** 6490970, 25036512 **Motorcraft** SWG-485


Red Light - Hot - ON at 251° F to 283° F

**No. 84236**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F.-S.A.E. short) 5/16" long.

 Replaces: **Delco** 1993445, 1993496, 1994061, D1867,  
 D1879, **G.M.** 6489179, 6489395, 6489766,  
 6490694, 6490970, 25036512  
**Motorcraft** SWG-1187, SWG-1340


Red Light - Hot - ON at 184° F to 216° F

**No. 84218**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F.-S.A.E. short) 5/16" long.


Red light - Hot - ON at 190° F to 210° F

**No. 84251**
**Mounting stem:** 3/8"-18 dryseal thread  
 (N.P.T.F.) .650" long.


Red Light - Hot - ON at 251°F to 283° F

**⊖ No. 84234**
**Mounting stem:** 1/2"-14 dryseal thread  
 (P.T.F.-S.A.E. short) 5/16" long.

 Supplied with terminal bullet assembly.  
 Replaces: **Delco** 1994095, D1866 **G.M.** 6490793


Red Light - Hot - ON at 245°F to 265° F

**No. 84248**
**Mounting stem:** 3/8"-18 dryseal thread  
 (N.P.T.F.) 3/8" long.

 Replaces: **Delco** D-1896 **G.M.** 8992347, 8993427,  
 25036035, 042, 139, 300, 371, 452, 468, 535  
**Motorcraft** SWG-2051


## Temperature Senders • For use with temperature gauge, self grounding.

Resistance at 220°F - 11.5 to 13.5 ohms

⊖ **No. 84204**

**Mounting stem:** 1/4"-18 dryseal thread  
(P.T.F.) 1/2" long.

Replaces: **Delco** 1994095, D1866 **G.M.** 6490793



Resistance at 220°F - 43 to 51 ohms

⊖ **No. 84201**

**Mounting stem:** 1/4"-18 dryseal thread  
(P.T.F.) 7/16" long.

Replaces: **A.M.** 3144585 **Chrysler** 1507050, 1770732,  
1842555, AL-14405A, 135550A, CH-2503 **Delco** C1850  
**Motorcraft** SW-338, SW-339



Resistance at 220°F - 91 to 111 ohms

⊖ **No. 84214**

**Mounting stem:** 1/2"-14 dryseal thread  
(P.T.F.) 9/16" long.

Replaces: **Delco** 1513130, G1851, G1857  
**G.M.** 6400759 **Motorcraft** SWG-342

